

Configuring Katana

Once you have RenderMan for Katana (RfK) installed there is minimal setup that you need in order to start generating renders! Before running Katana itself you'll need to set up your environment correctly after which Katana will automatically load the RfK plugin. Once in Katana you'll need to set up your scene with a camera and geometry, add RenderMan (PRMan) lights and materials then you're ready to render.



If multiple renderers are installed, to render with RenderMan, please set your `DEFAULT_RENDERER` environment variable to "prman"

Set Up Environment

In order to use RenderMan for Katana the path to the RfK plugin must be added to your `KATANA_RESOURCES` search path:

```
setenv KATANA_RESOURCES ${KATANA_RESOURCES}:${RfKTREE}/plugins/Resources/PRMan22
```

where `RfKTREE` is the install location for package. This tells Katana where to find the RfK plugin as well as the supporting modules needed for rendering and managing scenes.

RenderMan Nodes and Macros

The purpose of any Katana renderer plugin is to enable an artist to generate images using the full power of the given renderer. In order to start taking advantage of the RenderMan capabilities with the RenderMan plugin for Katana we need to start with a discussion of the PRMan-specific nodes and parameters:

PrmanGlobalStatements	This node contains most of the PRMan world state options. This is where you'll find settings such as pixelVariance , maxSamples .
PrmanObjectStatements	This is where object-specific PRMan attributes are set. Look here for visibility and trace attributes among others.
PrmanIntegratorSettings	This node controls settings relevant to each integrator. The separation of these controls allows for easier integration of your own custom integrator.
PrmanCameraSettings	This node controls per camera settings, such as depth of field and field of view.
PrmanDenoiseChannelDefine	This macro creates all the DisplayChannels required for the denoise utility.
PrmanDenoiseRenderOutputDefine	This macro is used for defining the outputs required by the multichannel OpenEXR that is used by the denoiser.
PrmanHoldoutCreate	This macro automates the process of setting up the AOVs and Sample Filters required for holdouts.
PrmanOutputChannelDefine	This node is used for defining arbitrary output variables (AOVs) used for outputting extra data from the shader or renderer during render calculations.
PrmanShadingNode	This shading node is used to add PRMan shaders (Bxdf's and Patterns) to a wider shading network (along with the NetworkMaterial node).
PrmanVolume	This node provides a simple interface to create either a volume box or import a vdb file.
Alembic_In_Prman	A multi-threaded node used to import/read Alembic Archives.

PRMan-specific Nodes