## **Aggregate Volumes in Katana**

Aggregate Volumes can decrease the render time for volumes by combining them into a single structure for the renderer to process. To get started with aggregate volumes in RfK, there are two steps: setting the aggregate name on the volume primitives and specifying a matching aggregate name in the integrator.

## Step One: Group volumes into aggregates with PrmanObjectStatements

First, add the volumes to the CEL group of PrmanObjectStatements. The volume locations can be added directly to the CEL, added via a custom expression, or set on an ancestor location (like /root) and inherited.

V Prman	)bjectStatementsss 🔳	PrmanObjectStatements	۲	\$ T	<b>ب</b> م	٩	•	PrmanObject	Statements1 🔳 🛛
targe	tMode CEL					-			CEL
▼ CEL (1	0			Ad	d Stateme	ents 🔻		▼ CEL (1) 🕲	
E O	Paths (2) Action					E 33		🗄 🕲 Custo	
/root/w /root/w	/orld/geo/bunny_cloud /orld/geo/volume							/root//*{attr('	'type") == "volume

Next, specify the aggregate name with the prmanStatements.primAttributes.volume.aggregate attribute. To begin with, give all volumes in the scene the same aggregate name. Volumes without an aggregate name will render, but will not be part of the aggregate structure.

▼ PrmanObjectStatements1 ■ Prman(					۶		
targetMode CEL							-
⊤ CEL (1) 🕲				Add	State	ement	ts 🔻
🖸 🕤 Custom							
/root//*{attr("type") == "volume"}							
<ul> <li>? ▶ attributes</li> </ul>							
⑦ ▼ primAttributes							
Orientation     inside							•
▶ curve							
▶ derivatives							
▶ dice							
▶ displacement							
▶ displacementbound							
▶ polygon							
▶ procedural							
▶ geometry							
subdivisionMesh							
▶ trace							
▶ trimcurve							
▼ volume							
L @ Aggregate globa	lVolumeAggregate						
DSO Min/Max &							
🗈 👁 Temporal Method 🛛 🗧 Euler	ian						-
ि 🖲 Frames per Second 🛛 🖥 🛽							
🖸 🕫 Shutter Offset 👌 1							
⑦ ▶ primvars							
> traversal							

## Step Two: Specify volume aggregate name in the integrator

PxrPathTracer has four parameters related to aggregate volumes. In the simple case, you'll only need to set the global "Volume Aggregate" parameter. But since the standard visibility attributes don't work within a volume aggregate, you may run into cases where you need to specify separate aggregate names for each type of visibility (camera, indirect, and transmission). These can be specified in the other three override parameters. If there is no aggregate specified in the integrator, or if the aggregate name specified in the integrator does not match the name set on a volume, the volume will not render.

V	P	rmanl	Integrator	Settings 🔳			atorSetti					-27	۶			
				create or	edit										-	
	Iocation  (root/integrators/default)														-	
			Active	E Yes											-	
	-	19.	ormaninter	ratorShade	er Pyrl	PathTra	cer						-	1 -	Q	
	Ě		, mannec <u>y</u>	Jiatorsnau		aanna										
				rect Bounce:	s 8	8										
				uation Dept	n b	-1										
			tochastic O	pacity Dept	n b	0										
						bxdf									-	
				ight Sample:	s 6	1										
				XDF Sample:	5 F	1										
				rect Sample:	s 6	1										
					s 5											
				ulate Opacity	, E											
				path guiding	а Б											
			ian Roulette													
			ect Clampir													
	•															
	L 💿 🛛 Volume Aggregate Name 🤤							balVo	lume	Aggreg	ate					
	🖸 🕐 Camera Aggregate Override															
	Indirect Aggregate Override															
	🔟 🖲 Transmission Aggregate Override															
							5									